



## Product Features:

- Most suitable for Fully front service installation
- Various pixel pitch available from P6.67, P8.33, P10
- Outdoor IP67 front and rear(aluminum module case)
- Ultra slim cabinet, save installation space for wall facade installation
- Fanless design, low noise running system

Model		IFX-660	IFX-800	IFX-100
Module Parameter	Pixel Pitch	P6.67mm	P8.33mm	P10mm
	Application	Outdoor	Outdoor	Outdoor
	Pixel Configuration	SMD2727	SMD3535	SMD3535
	Pixel Density (dots/m <sup>2</sup> )	22500	14400	10000
	Resolution (W×H)	60*45	48*36	40*30
	Dimension (mm)	400x300	400x300	400x300
Cabinet Parameter	Module qty (W×H)	2*3	2*3	2*3
	Resolution (W×H)	120*135	96*108	80*90
	Size (m <sup>2</sup> )	0.72	0.72	0.72
	Dimension (mm)	800x900mm	800x900mm	800x900mm
	Other cabinet size available	800x1200mm	800x1200mm	800x1200mm
	Weight (kg)	30	30	30
	Material	Aluminum cabinet and module case		
Curve Design	Available	Available	Available	
Screen Parameter	Brightness (nits)	6000-9000	7500-10000	6000-10000
	Color Temperature (K)	3200—9300 adjustable	3200—9300 adjustable	3200—9300 adjustable
	Viewing Angle (H/V°)	H: ±160°/V: ±110°	H: ±160°/V: ±110°	H: ±160°/V: ±110°
	Contrast	5000:1	5000:1	5000:1
	Max. Power Consumption (W/m <sup>2</sup> )	580	580	580
	Ave. Power Consumption (W/m <sup>2</sup> )	175	175	175
	Input Voltage (V)	AC100~240V, 47-63 (Hz)		
	Frame Frequency (Hz)	50-60	50-60	50-60
	Gray Scale	14-16bit	14-16bit	14-16bit
	Refresh Rate (Hz)	7680	7680	7680
	IP Grade	IP67	IP67	IP67
	Optimal Viewing Distance(m)	≥6.67m	≥8m	≥10m
	Working Temperature / Humidity (°C/RH)	-30 – 55 / 10%-90%RH	-30 – 55 / 10%-90%RH	-30 – 55 / 10%-90%RH
	Storage Temperature / Humidity (°C/RH)	-40 – 80 / 5%-95%RH	-40 – 80 / 5%-95%RH	-40 – 80 / 5%-95%RH
	Certification	CE, ROHS	CE, ROHS	CE, ROHS
	Lifespan	100,000H	100,000H	100,000H
	Signal Interface	DVI	DVI	DVI
Source Compatibility	YPbPr, PAL/NTSC, S-Video, HDMI, VGA,	YPbPr, PAL/NTSC, S-Video, HDMI, VGA,	YPbPr, PAL/NTSC, S-Video, HDMI, VGA,	
Maintenance type	Fully Front or Rear	Fully Front or Rear	Fully Front or Rear	